

FINE FISSURED Ceramaguard / medium texture




FINE FISSURED Ceramaguard with PeakForm 24mm Exposed Tee grid

Armstrong Grid Options with FINE FISSURED



FINE FISSURED Ceramaguard with PeakForm 24mm Exposed Tee grid



Square Lay-in with Peakform Grid



FINE FISSURED Ceramaguard / medium texture



Sustainable Performance

- Green Star points may also be achieved using Armstrong ceilings (contact your Armstrong office for details)
- Recycled Content 42% PeakForm Grid: 25%
- Fully Recyclable at end of life:

Key Selection Attributes

- Nondirectional visual reduces installation time and scrap
- Guaranteed resistance to chemical fumes and scrubbing
- Durable Scrubbable Washable
- **HumiGuard Max** performance – Sag-resistant formulation to withstand chemical fumes and extreme temperatures up to 49°C (including steam up to 135°C) and relative humidity up to 100%, including standing water applications

Typical Applications

- Laboratories
- Locker rooms, shower areas
- Indoor pools
- Outdoor soffits and canopies
- Parking garages
- Hydrotherapy
- Exterior Soffits (see note under Application Considerations)
- Marine Use

Visual Selection

Performance Selection

Grid Face	Edge Profile	Item Number	Dimensions	Acoustics		Anti-Mold/ Mildew	Sag Resist	Light Reflect	Installed Cost
				NRC	CAC				
FINE FISSURED Ceramaguard									
24mm	Square lay-in	607M6	600 x 600 x 15mm	0.55	38			0.82	\$\$\$
		608M6	600 x 1200 x 15mm	0.55	40			0.82	\$\$\$



Physical Data

Material
Ceramic and mineral fiber composite

Surface Finish
Scrubable factory-applied vinyl plastic paint with "BioBlock™ mold/mildew inhibitor"

Flame Spread/Fire Resistance
Conforms to BCA Spec. C1.10 and tested to AS/NZS 3837: 1998 – "Group 1" AS/NZS 1530.3

Thermal Resistance
R Value: 0.25 m²K/W

Anti Mold / Mildew & Bacteria
"BioBlock™ Plus" contains an antimicrobial treatment, providing resistance against growth of mold/mildew and Gram-positive and Gram-negative odour/stain causing bacteria.

Weight
(6.86 kgs/m²)

Recommended Suspension Systems
PeakForm XL 24mm Exposed Tee grid
"Quick Lock™" Extruded Aluminium Tee grid with stainless steel joining components and suspension wire – for use over swimming pools and other wet/corrosive environments

Application Considerations
For Exterior soffit and marine applications, wind uplift should be considered