

# FINE FISSURED / medium texture



FINE FISSURED 1200 x 600mm Square Edge with PeakForm 24mm Exposed Tee grid

## Armstrong Grid Options with FINE FISSURED




FINE FISSURED Square Edge with PeakForm 24mm Exposed Tee Grid




FINE FISSURED Tegular Edge with PeakForm 24mm Exposed Tee Grid




FINE FISSURED Tegular Edge with Silhouette 15mm Grid




FINE FISSURED K2C2 / Square Edge with Aluminium Top Hat Modular Grid




Square Lay-in with PeakForm Grid




Angled Tegular with PeakForm Grid



Beveled Tegular with Suprafine XL Grid



Beveled Tegular with Silhouette Grid



K2C2 Edge and Top Hat Grid



# FINE FISSURED / medium texture



## Sustainable Performance

- GLOBAL GREEN TAG<sup>Cert™</sup> Certified Product:
  - Achieving Green Rate Level A: Certified to provide 100% Credit Points in the GBCA & NZGBC Green Star Materials Calculators
  - IEQ; Contributes to the “Low VOC Emission” credit
- Listed by Ecospecifier, and deemed to be of an eco-preferable nature and likely to contribute to the achievement of various Green Star points:
- Recycled Content 36–54% PeakForm Grid: 25%
- ISO 14001 EMS compliant manufacturing
- Fully Recyclable at end of life:

## Key Selection Attributes

- Cost effective ceiling solution
- High Acoustic performance options
- Reliable, proven performance
- High Light Reflectance
- **HumiGuard Plus** performance – Sag-resistant formulation to withstand temperatures between 0°C–49°C and relative humidity up to 99%
- **BioBlock™ Plus** paint on face and back of HumiGuard panels to inhibit or retard growth of mold/mildew and bacteria on painted surface

## Typical Applications

- Office area
- Retail
- Healthcare spaces
- Public areas
- Education

## Visual Selection

## Performance Selection

Grid Face	Edge Profile	Item Number	Dimensions (Nom)	Acoustics		Anti-Mold/ Mildew	Sag Resist	Light Reflect	Installed Cost	
				NRC/Alpha W	CAC/Dnfw					
<b>FINE FISSURED</b>										
15mm	Beveled Tegular	1734MS	600 x 600 x 16mm		0.55/0.55	35/33			0.85	\$
24mm	Angled Tegular	3572S	600 x 600 x 16mm		0.55/0.55	35/33			0.85	\$
		3574S	600 x 1200 x 16mm		0.55/0.55	35/33			0.85	\$
24mm	Square Lay-in	1730S	24 x 48 x 5/8		0.55/0.55	33/31			0.85	\$
		3570S	600 x 1200 x 16mm		0.55/0.55	33/31			0.85	\$
32mm	Top Hat Grid	K2C2 Edge with Concealed Spline*	400 x 1200mm 450 x 1350mm 500 x 1500mm Other		0.55/0.55+	35/35			0.85	\$\$
<b>FINE FISSURED – High Acoustic</b>										
24mm	Square Lay-in	1714MEX	600 x 1200 x 19mm		0.70/0.60MH	40/40			0.85	\$\$
		4121S	600 x 1200 x 20mm		0.70/0.70H	35/32			0.85	\$\$
24mm	Angled Tegular	4122S	600 x 600 x 20mm		0.70/0.70	35/32			0.85	\$\$
		4123S	600 x 1200 x 20mm		0.70/0.70	35/32			0.85	\$\$

- Available in other sizes and performance options.
- + Available in NRC/Alpha W 0.70

## Physical Data

**Material**  
Wet-formed mineral fiber

**Surface Finish**  
Factory-applied vinyl latex paint with BioBlock™ mold/mildew inhibitor

**Flame Spread/Fire Resistance**  
Conforms to BCA Spec. C1.10 and tested to AS/NZS 3837: 1998 – “Group 1”, AS/NZS 1530.3

**Thermal Resistance**  
R Value: 0.26 m<sup>2</sup>K/W

**Anti Mold / Mildew & Bacteria**  
“BioBlock™ Plus” contains an antimicrobial treatment, providing resistance against growth of mold/mildew and Gram-positive and Gram-negative odour/stain causing bacteria.

**Weight**  
1730S, 3570S, 3510S – 3.1 kgs/m<sup>2</sup>  
3572S, 3574S, 1734MS – 3.53 kgs/m<sup>2</sup>  
4121S – 5.07 kgs/m<sup>2</sup>  
1714MEX – 6.13 kgs/m<sup>2</sup>

**Recommended Suspension System**

Items	Suspension System
3572S, 3574S	24mm PeakForm Exposed Tee
1730S, 3570S	
4121S, 4122S	
4123S,	
1714MEX	
1734MS	15mm Suprafine Exposed Tee
	15mm Silhouette Grid

Other Armstrong suspension systems, including, “Blue Tongue” Aluminium, available upon request.

