

ULTIMA® / very fine texture



Ultima with Suprafine 15mm Exposed Tee grid


Armstrong Grid Options with ULTIMA®




ULTIMA Square Edge with PeakForm 24mm Exposed Tee Grid




ULTIMA Tegular Edge with SUPRAFINE 15mm Exposed Tee Grid




ULTIMA Tegular Edge with 15mm SILHOUETTE Grid




ULTIMA K2C2 / Square Edge with Aluminium Top Hat Modular Grid




Square Lay-in with Peakform Grid




Beveled Tegular with Peakform Grid



Beveled Tegular with Suprafine XL Grid



Beveled Tegular with SILHOUETTE Grid



K2C2 Edge and Top Hat Grid



ULTIMA[®] / very fine texture



Sustainable Performance

- GLOBAL GREEN TAG^{cert}™ Certified Product:
 - Achieving Green Rate Level A: Certified to provide 100% Credit Points in the GBCA & NZGBC Green Star Materials Calculators
 - IEQ; Contributes to the “Low VOC Emission” credit
- Listed by Ecospecifier, and deemed to be of an eco-preferable nature and likely to contribute to the achievement of various Green Star points:
- Recycled Content:
 - Ultima: 62-75% PeakForm Grid: 25%
- ISO 14001 EMS compliant manufacturing
- Fully Recyclable at end of life:

Key Selection Attributes

- High Acoustical performance
- DuraBrite toughened scrim for panel longevity and lower lifecycle costs
 - Scratch-resistant
 - Scrubbable
 - Soil-resistant
- High light reflective finish (LR 0.90) reducing lighting and energy costs
- Smooth non-directional, white finish
- **HumiGuard Plus** performance – Sag-resistant formulation to withstand temperatures between 0°C 49°C and relative humidity up to 99%
- **BioBlock™** paint on face and back of HumiGuard panels to inhibit or retard growth of mold/mildew on painted surface

Typical Applications

- Offices
- Healthcare
- Education
- Retail
- Call Centres
- Conference Rooms
- Auditoriums
- Corridors and Lobbies

Visual Selection

Performance Selection

Grid Face	Edge Profile	Item Number	Dimensions	Acoustics		Anti-Mold/ Mildew	Sag Resist	Light Reflect	Installed Cost	
				NRC/Alpha W	CAC/Dnfw					
ULTIMA[†]										
15mm	Beveled Tegular	H4778	600 x 600 x 19mm		0.70/0.65H	39/36			0.90	\$\$\$
		H4779	600 x 1200 x 19mm		0.70/0.65H	39/36			0.90	\$\$\$
24mm	Beveled Tegular	SC97281	600 x 600 x 19mm		0.70/0.65H	39/36			0.90	\$\$\$
		SC97282	600 x 1200 x 19mm		0.70/0.65H	39/36			0.90	\$\$\$
24mm	Square Lay-in	H4770	600 x 600 x 19mm		0.70/0.65H	39/36			0.90	\$\$\$
		H4771	600 x 1200 x 19mm		0.70/0.65H	39/36			0.90	\$\$\$
32mm	Top Hat Grid	K2C2 Edge with concealed Spline*	400 x 1200mm 450 x 1350mm 500 x 1500mm Other		0.70/0.65H	39/36			0.90	\$\$\$

- Light reflectance values shown as averages.
- Other sizes available upon request.

Physical Data

Material
Wet-formed mineral fiber with DuraBrite acoustically transparent membrane

Surface Finish
DuraBrite with factory-applied acrylic latex paint with "BioBlock™ mold/mildew inhibitor"

Flame Spread/Fire Resistance
Conforms to BCA Spec. C1.10 and tested to AS/NZS 3837: 1998 – "Group 1" AS/NZS 1530.3

Thermal Resistance
R Value: 0.39 m²K/W

Anti Mold / Mildew & Bacteria
"BioBlock™ Plus" contains an antimicrobial treatment, providing resistance against growth of mold/mildew and Gram-positive and Gram-negative odour/stain causing bacteria.

Weight
All Items – 4.9 kgs/m²

Items	Suspension System
SC97281	24mm Peakform
SC97282	Exposed Tee
H4770	
H4771	

H4778	15mm Suprafine
H4779	Exposed Tee

H4778	15mm Silhouette Grid
H4779	

Other Armstrong suspension systems, including, "Blue Tongue" Aluminium, available upon request.

